



LEDTEC

LSPE-01S Enclosure Box

TECHNICAL DATA SHEET

Ledtec Surge Protection Enclosures are water resistant junction boxes designed for multi purpose termination and surge protection. Designed for durability and optimal performance, it includes waterproofing and high impact resistance allowing long lasting protection. With multi configurations possible including 1, 2 or 3 circuit protection as well single or double surge protection, it is the optimal solution for your electrical termination needs.

Areas for Application

- Outdoor Installations
- Industrial Environments
- Commercial Installation
 - Public Installation



G & S Industries

97 Guthrie Street,
Osborne Park, WA

[Website Link](#)

TECHNICAL SPECIFICATIONS

Product		Material & Finish	
Model	LSPE-01S	Ingress Protection Rating	IP66
Description	Ledtec Surge Protection Enclosure	Impact Rating	IK10
		Material Composition	Polyvinyl Chloride (PVC)
		Material Composition (Driver Box)	Casting aluminium
		Finish	Grey (RAL 7035)
Product Information		Weight & Packaging	
Number of Gangs	3 Gangs	Product Dimensions	292 x 100 x 63mm
Operating Temperature Range	-40° ~ +90 ° c	Packaged Weight	1.4kg
Mounting	Inside Pole Flash Mounted		
Electrical Characteristics		Warranty	
Top Glands	M20 IP68	Warranty	5 years
Top Adaptors	M25-M20		
Terminal	COPAK BD3		
Circuit Breaker	1x 6A Schneider MCB		
Terminals	Phoenix Terminals 2x 25 / 16 L1 / N1 / PE		
Bottom Glands	M25 IP68		
Surge Protector	CITEL DS89L-230G/2L		

